
24 134 AL3 **ATRIO THERMOSTATIC MIXER FOR 1 OUTLET WITH SHUT OFF VALVE**






TOOTE KIRJELDUS

- Värvus: brushed hard graphite
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE Long-Life finish
- wall escutcheon with GROHE FastFixation (covered escutcheon- and shaft sealing, covered fixing)
- metal escutcheon, retroactively 6° adjustable
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valves and dirt strainers
- ceramic stop valve, 120°
- metal handles
- flow performance: outlet B = 27 l/min outlet C = 30 l/min
- without roughing-in-set

24 134 AL3 **ATRIO THERMOSTATIC MIXER FOR 1 OUTLET WITH SHUT OFF VALVE**



VARUOSAD, jaanuar 2018 – nüüd

1: Mounting plate (Tellimuse number 49080000)

2: Temperature control handle (Tellimuse number 49089AL0)

3: Escutcheon (Tellimuse number 49073AL0)

4: Shut-off handle Aquadimmer (Tellimuse number 49090AL0)

5: Aquadimmer (Tellimuse number 49084000)

6: Thermostatic compact cartridge 3/4" (Tellimuse number 49028000)

7: Non-return valve (Tellimuse number 49085000)

8: Seal (Tellimuse number 48360000)

9: GROHE TurboStat cartridge 3/4" (Tellimuse number 49003000)*

10: Service stops (Tellimuse number 1405300M)*

11: Socket spanner (Tellimuse number 49059000)*

12: Backflow protection combination (DIN-EN1717) (Tellimuse number 14055000)*

13: Universal extension set 2-handle thermostats, 25 mm (Tellimuse number 14058000)*

* Lisatarvikud