


24 358 GL0 ATRIO THERMOSTATIC SHOWER MIXER FOR 2 OUTLETS WITH INTEGRATED SHUT OFF/DIVERTER VALVE



TOOTE KIRJELDUS

- Värvus: cool sunrise
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE Long-Life finish
- wall escutcheon with GROHE FastFixation (covered escutcheon- and shaft sealing, covered fixing)
- metal escutcheon, retroactively 6° adjustable
- printed head and hand shower symbol
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- GROHE AquaDimmer, integrated shut off/diverter valve
- metal handles
- without roughing-in-set
- flow performance: outlet B = 27 l/min outlet C = 30 l/min



24 358 GL0 ATRIO THERMOSTATIC SHOWER MIXER FOR 2 OUTLETS WITH INTEGRATED SHUT OFF/DIVERTER VALVE



VARUOSAD, oktoober 2021 – nüüd

- 1: Mounting plate (Tellimuse number 49080000)
- 2: temperature control handle (Tellimuse number 49089GL0)
- 3: Escutcheon (Tellimuse number 49246GL0)
- 4: shut-off handle aquadimmer (Tellimuse number 49090GL0)
- 5: Aquadimmer (Tellimuse number 49084000)
- 6: Thermostatic compact cartridge 3/4" (Tellimuse number 49028000)
- 7: Non-return valve (Tellimuse number 49085000)
- 8: Seal (Tellimuse number 48360000)
- 9: GROHE TurboStat cartridge 3/4" (Tellimuse number 49003000)*
- 10: Service stops (Tellimuse number 1405300M)*
- 11: Socket spanner (Tellimuse number 49059000)*
- 12: Backflow protection combination (DIN-EN1717) (Tellimuse number 14055000)*
- 13: Universal extension set 2-handle thermostats, 25 mm (Tellimuse number 14058000)*

* Lisatarvikud