



26 446 LS0 RAINSHOWER SYSTEM SMARTCONTROL MONO 360 COMBI SHOWER SYSTEM WITH THERMOSTAT, EXPOSED/CONCEALED



TOOTE KIRJELDUS

- Värvus: moon white/chrome
- consisting of:
 - exposed/concealed SmartControl thermostat
 - allows change between:
 - head shower Rainshower Mono 360 with horizontal 450 mm shower arm, spray plate white
 - GROHE PureRain/GROHE Rain O2 spray*
 - maximum flow rate (at 3 bar): 20 l/min
- Power&Soul 130 hand shower, spray plate white (27 673)
 - maximum flow rate (at 3 bar): 9.5 l/min
- hand shower wall holder (27 055)
- Silverflex shower hose 1.500 mm (28 364)
- minimum flow rate 10 l/min.
- GROHE DreamSpray perfect spray pattern
- GROHE Long-Life finish
- GROHE CoolTouch no risk of scalding
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE Water Saving - Less water, perfect flow
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C included
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- GROHE EasyReach shower tray
- SpeedClean anti-lime system
- TwistStop to prevent hose from twisting
- requires rough-in set 26 264 001 and concealed unit 26 449 000 – all to be ordered separately
- * to be decided at first installation; factory default setting: GROHE PureRain