


## 29 118 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH ONE VALVE




### TOOTE KIRJELDUS

- Värvus: chrome
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE ProGrip with knurl structure
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valves and dirt strainers
- without roughing-in-set
- flow performance: outlet A (to external shut-off) = 34 l/min outlet B/C = 29 l/min



## 29 118 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH ONE VALVE



### VARUOSAD, jaanuar 2020 – nüüd

- 1: Mounting plate (Tellimuse number 48362000)
- 2: Temperature control handle (Tellimuse number 49029000)
- 3: Escutcheon (Tellimuse number 49030000)
- 4: Push button (Tellimuse number 48361000)
- 5: Cartridge (Tellimuse number 48359000)
- 5.1: Spindle (Tellimuse number 49088000)
- 6: Thermostatic compact cartridge 3/4" (Tellimuse number 49028000)
- 7: Non-return valve (Tellimuse number 49085000)
- 8: Seal (Tellimuse number 48360000)
- 9: Socket spanner (Tellimuse number 49059000)\*
- 10: GROHE TurboStat cartridge 3/4" (Tellimuse number 49003000)\*
- 11: Service stops (Tellimuse number 1405300M)\*
- 12: Universal extension set single-lever mixers, 25 mm (Tellimuse number 14048000)\*

\* Lisatarvikud