

29 124 DC0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES



TOOTE KIRJELDUS

- Värvus: supersteel
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to full flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valves and dirt strainers
- multiple outlets can be run simultaneously
- without roughing-in-set
- flow performance: outlet B = 24 l/min outlet C = 26 l/min outlet B+C = 29 l/min

29 124 DC0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES



VARUOSAD, juuli 2018 – nüüd

- 1: Mounting plate (Tellimuse number 48363000)
- 2: Temperature control handle (Tellimuse number 49029DC0)
- 3: Escutcheon (Tellimuse number 49039DC0)
- 4: Push button (Tellimuse number 48361DC0)
- 5: Cartridge (Tellimuse number 48359000)
- 5.1: Spindle (Tellimuse number 49088000)
- 6: Thermostatic compact cartridge 3/4" (Tellimuse number 49028000)
- 7: Non-return valves (Tellimuse number 47979000)
- 8: Seal (Tellimuse number 48360000)
- 9: Socket spanner (Tellimuse number 49059000)*
- 10: Backflow protection combination (DIN-EN1717) (Tellimuse number 14055000)*
- 11: GROHE TurboStat cartridge 3/4" (Tellimuse number 49003000)*
- 12: Service stops (Tellimuse number 1405300M)*
- 13: Universal extension set single-lever mixers, 25 mm (Tellimuse number 14048000)*

* Lisatarvikud