

37 157 000 **FLUSH VALVE FOR WC**



TOOTE KIRJELDUS

- concealed installation
- $\frac{3}{4}$ "
- stop valve
- 6 - 14 l adjustable
- for low pressure
- for wash-down and wash-out bowls
- flow pressure range from 0.6 - 3.0 bar (min. static pressure 1.5 bar)
- with flow rate adjustment
- box for concealed installation with flush elbow
- flush pipe adjustable in length
- without wall plate/actuation



37 157 000 FLUSH VALVE FOR WC



VARUOSAD, juuli 2008 – nüüd

- 1: Hand wheel (Tellimuse number 43043000)
- 2: Cover (Tellimuse number 43122000)
- 3: Piston (Tellimuse number 43451000)
- 3.1: Sleeve (Tellimuse number 4376900M)
- 4: Supply stop (Tellimuse number 43405000)
- 5: Safety valve (Tellimuse number 43422000)
- 5.1: Membrane (Tellimuse number 4377300M)
- 6: Operating rod (Tellimuse number 43067000)
- 7: Discharge sleeve (Tellimuse number 43326000)
- 8: Throttle nozzle (Tellimuse number 43408000)
- 9: Set of seals (Tellimuse number 43012000)*

* Lisatarvikud