


## 38 915 LS0 **GROHE ONDUS DIGITECTURE LIGHT FLUSH PLATE**



### TOOTE KIRJELDUS

- Värvus: moon white
- for dual flush or start & stop actuation
- for SoftTouch flushing activation
- external highlighted outline
- with LEDs in blue, red, yellow, green
- light colour individually adjustable
- on/off timer for individual regulation of illuminating period
- 3 m connecting cable
- transformer for external installation
- 110 V to 240 V 50/60 Hz broad range power supply
- 9 VA
- CE approved
- for GD 2 cisterns with pneumatic discharge valve AV1
- 200 x 200 mm
- made of security glass
- GROHE Water Saving - Less water, perfect flow
- not suitable for GROHE Fresh

## 38 915 LS0 GROHE ONDUS DIGITECTURE LIGHT FLUSH PLATE

**VARUOSAD**, august 2010 – nüüd

- 1: Top plate with electronic (Tellimuse number 42427LS0)
- 2: Servo motor (Tellimuse number 43281000)
- 2.1: Support device (Tellimuse number 42246000)
- 2.2: Motor support device (Tellimuse number 43617000)
- 3: Hose (Tellimuse number 43307000)
- 4: Plug power supply 110-240 V (Tellimuse number 36078000)
- 5: Mounting set (Tellimuse number 43306000)
- 6: Extension cable (Tellimuse number 36221000)
- 7: Extension cable (Tellimuse number 36222000)\*

\* Lisatarvikud

