

## 39 376 000 **RAPID SL ELEMENT FOR URINAL WITH TEMPERATURE SENSOR**



### TOOTE KIRJELDUS

- with roughing-in set for T sensor
- 1.13 and 1.30 m installation height
- for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- height adjustable fitting connections
- quick adjustment, lockable
- fixing material
- TÜV approved
- HT-outlet bend Ø 50 mm
- fixing bolts M8, with fixing device for ceramic
- inlet connection and inlet connecting set
- box for concealed installation including roughing-in box
- water group with stop valve and flush elbow
- for T sensor electronic please order installation set 39 368 000 or 39 369 000 (sold separately)
- for on-the-wall installation please order wall brackets 38 558 00M (sold separately)



## 39 376 000 **RAPID SL ELEMENT FOR URINAL WITH TEMPERATURE SENSOR**

**VARUOSAD**, mai 2015 – nüüd

- 1: Outlet elbow 2" (Tellimuse number 42943000)
- 1.1: Holder for outlet elbow (Tellimuse number 42236000)
- 2: Switching power supply (Tellimuse number 42470000)
- 3: Fixation (Tellimuse number 4307500M)
- 4: Threaded bolt (Tellimuse number 43078000)
- 5: Lip seal (Tellimuse number 4387500M)
- 6: Wall brackets (Tellimuse number 3855800M)

